

aPower 2

AC-coupled battery

Store solar generated power while the sun is shining. Store grid energy during lower rate periods. Use the stored energy when needed to lower electric bills. Run heavy loads such as air conditioners and water heaters as usual even during grid outages. Provide homeowner peace of mind by fully charging before severe weather events. The aPower 2 also supports parallel AC-coupled connection with FranklinWH aPower S batteries to expand power and capacity for homes at the same time.

The system is off-grid ready, designed to operate independently from the main power grid to deliver reliable energy in any situation.



- ✓ 10 kW continuous / 15 kW peak for 10s
- ✓ 8 kW charge power

- ✓ Safer LFP battery cell chemistry 15 kWh AC¹ per unit, up to 225 kWh (15 units) per aGate
- ✓ 15-year or 60 MWh throughput warranty

PERFORMANCE SPECIFICATIONS

Basic Information

Name	aPower 2
SKU	APR-10K15V2-US
Nameplate Model	Power X-20
Certification / CEC Listing Name	aPower Xyyy
Battery Chemistry	Lithium Iron Phosphate (LFP)
Usable System Energy	15 kWh AC ¹ per unit, up to 15 units per aGate
Aggregate Warrantied Throughput	60 MWh
Real Power (charge)	8 kW continuous (/on-grid/off-grid)
Real Power (Discharge)	10 kW / 11.5 kVA continuous (/on-grid/off-grid)
Nominal AC Voltage	120 / 240 V, 120 / 208 V (single phase), 60 Hz
Grid Voltage Range	211 ~ 264 Vac; 183 V ~ 228 Vac
Coupling	AC-Coupled
Phase	2 W+N+PE
Round Trip Efficiency (Grid - Battery - Load)	90% ¹
Maximum Short-Circuit Current Rating	10 kA
Work Modes	Self-Consumption Time of Use Emergency Backup
Noise Emission	30 dBA Typical 45 dBA Maximum
Flood Resistance (IP67)	Up to 29" from the aPower 2 base
User Interface	FranklinWH App
Warranty ²	15 years

Grid-Tied Specifications

Nominal Output Power (AC)	5 kW	7.6 kW	9.6 kW	10 kW
Maximum Apparent Power	5 kVA	7.6 kVA	9.6 kVA	11.5 kVA
Maximum Continuous Current	21 A	32 A	40 A	48 A
Overcurrent Protection Device	30 A	40 A	50 A	60 A

Off-grid Specifications³

THDU	< 1%
Voltage Regulation Accuracy	±1%
Frequency Accuracy	±0.1 Hz
Half-Wave Load Capability	5 kW
Peak Output Power	15 kW @ 10 S
Transient load capacity	25 kW @ 1 S
Load Imbalance Ratio	100%
Load Start Capability	185 A LRA


1. At beginning of life: 3 kW charge/discharge power, 77° F (25° C).

2. For more details, please refer to the FranklinWH System Limited Warranty for End Users available in the Documentation Center on the FranklinWH website.

3. Output performance is designed with reference to IEC 62040-3 (Uninterruptible Power Systems - Part 3: Method of specifying the performance and test requirements). A number of core indicators meet the requirements of high-performance UPS.

COMPLIANCE INFORMATION

Certifications	UL 9540, UL 9540A, UL 1973, UL 1741, UL1741 SB, UL 1741 PCS, UL 60730-1, IEEE 1547, IEEE 1547.1, UN 38.3, CSA C22.2 No. 107.1:16
Seismic	AC 156, OSHPD, IEEE 693-2005 (high)
Environmental	California Proposition 65 RoHS Directive 2011 / EU
Emissions	FCC Part 15 Class B, ICES 003



MECHANICAL SPECIFICATIONS

Dimensions (H x W x D)	45.2 in x 29.5 in x 11.8 in (1149 mm x 750 mm x 300 mm)
Weight, aPower 2 Complete	357 lb. (162 kg)
Weight, without Cover	335 lb. (152 kg)
Weight, Cover	22 lb. (10 kg)
Mounting	Wall or floor mount
Cooling	Natural air-cooled design

ENVIRONMENTAL SPECIFICATIONS

Enclosure Type	Type 3R
Ingress Protection	IP56 (Wiring) IP67 (Battery Pack & Inverter)
Operating Temperature	-4 °F to 122 °F (-20 °C to 50 °C) Operates up to 131 °F (55 °C) at 5kW derated output
Operating Humidity (RH)	Up to 100% RH, condensing
Altitude	Maximum 9,843 ft (3,000 m)
Environment	Indoor and outdoor rated

The aPower 2 (SKU: APR-10K15V2-US) is available in the United States and Canada. For product availability in other regions, please visit our official website or contact a local authorized dealer.

